

# Spartan<sup>®</sup> RV Chassis Advanced Protection System<sup>™</sup> (APS):

- Automatic Traction Control (ATC)
- Electronic Stability Control (ESC)
- OPTIONAL Collision Mitigation System (CMS) with Adaptive Cruise Control (ACC)
- Mobileye® visual & audible lane departure warning
- Tire Pressure Monitoring System (TPMS)
- Spartan RV Chassis Safe Haul<sup>®</sup> (The industry's premier factorychassis integrated air supply for tow vehicle brake systems.)

# Premium Features:

- Comfort Drive<sup>™</sup> steering assist system w/ variable driver's effort control feature
- Variable Geometry Turbo (VGT) exhaust brake
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- 10,000 lb towing capacity
- Tri-Pod Steering Wheel with leather finish, phone, and media controls

- Connected Coach® 12.3" glare-free digital dash display
- Suspended adjustable pedals
- 20-Year Transferable Warranty on Frame & Cross Members
- 5-year/100,000-mile transferable warranty
- 5-year/100,00-mile Cummins Engine warranty
- 5-year/200,000-mile Allison Transmission warrant

# Specifications:

Engine	
Cummins L9	
18.7 CFM Air Compressor	
1,000 Watt Block Heater	
Peak HP:	380 HP @ 2,200 rpm
Peak Torque:	1,150 lb-ft @ 1,200 rpm

# Transmission

Allison 3000 MH

# **Chassis Ratings**

	35'	38'
GVWR:	38,000 lb	38,600 lb
Front GAWR:	14,000 lb	14,600 lb
Rear GAWR:	24,000 lb	24,000 lb
GCWR:	48,000 lb	48,600 lb

#### Suspension

Front:	Integrated air suspension and steer axle system
	with 14,600 lb capacity
Rear:	Non-torque reactive parallelogram air suspension
	with 24,000 lb capacity

 Brakes

 ABS:
 WABCO 4S/4M with ESC

 Front:
 Air disc

 Drive:
 Air drum

Koni

Koni

# Steering

Shocks

Front:

Rear:

Comfort Drive<sup>™</sup> steering assist system with manual tilt & telescoping column

#### **Fuel System**

Fuel Tank:100 gallon with dual fillDEF Tank:10 gallon

# **Electrical System**

12v electrical system Batteries: Two 950 cca Alternator: 210 amp

# Cooling System

Rear-mounted radiator: parallel airflow system with low-profile radiator

Frame

Raised rail design for frame strength and basement storage

# Tires

Michelin XRV 305/70R22.5 LRL

# Wheels

(4) Aluminum wheels with Accu-Shield® Finish and dress kit(2) Steel wheels on inside duals

# Wheelbase

35': 212" 38': 248"