



**Spartan® RV Chassis Advanced Protection System™ (APS):**

- Automatic Traction Control (ATC)
- Electronic Stability Control (ESC)
- **OPTIONAL** Collision Mitigation System (CMS) with Adaptive Cruise Control (ACC)
- Mobileye® visual & audible lane departure warning
- Tire Pressure Monitoring System (TPMS)
- Spartan RV Chassis Safe Haul® (The industry’s premier factory-chassis integrated air supply for tow vehicle brake systems.)

**Premium Features:**

- Comfort Drive™ steering assist system w/ variable driver’s effort control feature
- Variable Geometry Turbo (VGT) exhaust brake
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- 10,000 lb towing capacity
- Tri-Pod Steering Wheel with leather finish, phone, and media controls
- Connected Coach® 12.3” glare-free digital dash display
- Suspended adjustable pedals
- 20-Year Transferable Warranty on Frame & Cross Members
- 5-year/100,000-mile transferable warranty
- 5-year/100,000-mile Cummins Engine warranty
- 5-year/200,000-mile Allison Transmission warrant

**Specifications:**

**Engine**

Cummins L9  
 18.7 CFM Air Compressor  
 1,000 Watt Block Heater  
 Peak HP: 380 HP @ 2,200 rpm  
 Peak Torque: 1,150 lb-ft @ 1,200 rpm

**Transmission**

Allison 3000 MH

**Chassis Ratings**

	35'	38'
GVWR:	38,000 lb	38,600 lb
Front GAWR:	14,000 lb	14,600 lb
Rear GAWR:	24,000 lb	24,000 lb
GCWR:	48,000 lb	48,600 lb

**Suspension**

Front: Integrated air suspension and steer axle system with 14,600 lb capacity  
 Rear: Non-torque reactive parallelogram air suspension with 24,000 lb capacity

**Shocks**

Front: Koni  
 Rear: Koni

**Brakes**

ABS: WABCO 4S/4M with ESC  
 Front: Air disc  
 Drive: Air drum

**Steering**

Comfort Drive™ steering assist system with manual tilt & telescoping column

**Fuel System**

Fuel Tank: 100 gallon with dual fill  
 DEF Tank: 10 gallon

**Electrical System**

12v electrical system  
 Batteries: Two 950 cca  
 Alternator: 210 amp

**Cooling System**

Rear-mounted radiator: parallel airflow system with low-profile radiator

**Frame**

Raised rail design for frame strength and basement storage

**Tires**

Michelin XRV 305/70R22.5 LRL

**Wheels**

(4) Aluminum wheels with Accu-Shield® Finish and dress kit  
 (2) Steel wheels on inside duals

**Wheelbase**

35': 212"  
 38': 248"