



Spartan® RV Chassis Advanced Protection System™ (APS):

- Automatic Traction Control (ATC)
- Electronic Stability Control (ESC)
- **OPTIONAL** Collision Mitigation System (CMS) with Adaptive Cruise Control (ACC)
- Mobileye® visual & audible lane departure warning
- Tire Pressure Monitoring System (TPMS)
- Spartan RV Chassis Safe Haul® (The industry's premier factory-chassis integrated air supply for tow vehicle brake systems.)

Premium Features:

- Comfort Drive™ steering assist system w/ variable driver's effort control feature
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- Connected Coach® 12.3" glare-free digital dash display
- Passive steer tag axle
- 15,000 lb towing capacity
- 3-stage engine compression brake
- Tri-Pod Steering Wheel with leather finish, phone, and media controls
- 20-Year Transferable Warranty on Frame & Cross Members
- 5-year/100,000-mile transferable warranty
- 5-year/100,000-mile Cummins Engine warranty
- 5-year/200,000-mile Allison Transmission warranty

Specifications:

Engine

Cummins L9
 18.7 CFM Air Compressor
 1,000 Watt Block Heater
 Peak HP: 400 HP @ 2,200 rpm
 Peak Torque: 1,250 lb-ft @ 1,200 rpm

Transmission

Allison 3000 MH

Chassis Ratings

| | 40' | 43' |
|-------------|-----------|-----------|
| GVWR: | 44,600 lb | 46,000 lb |
| Front GAWR: | 14,600 lb | 16,000 lb |
| Rear GAWR: | 20,000 lb | 20,000 lb |
| Tag GAWR: | 10,000 lb | 10,000 lb |
| GCWR: | 59,600 lb | 61,000 lb |

Suspension

40' Front: Integrated air suspension and steer axle system with 14,600 lb capacity
 43' Front: Trailing beam air suspension with 16,000 lb capacity
 Rear: Non-torque reactive parallelogram air suspension with 20,000 lb capacity
 Tag: Parallelogram air suspension and integrated passive steering tag axle with 10,000 lb capacity

Shocks

Front: Koni
 Rear: Koni
 Tag: Koni

Brakes

ABS: WABCO 6S/6M with ESC
 Front: Air disc
 Drive: Air drum
 Tag: Air drum

Steering

Comfort Drive™ steering assist system with manual tilt & telescoping column

Fuel System

Fuel Tank: 100 gallon with dual fill
 DEF Tank: 10 gallon

Electrical System

12v electrical system
 Batteries: Two 950 cca
 Alternator: 210 amp

Cooling System

Rear-mounted radiator: parallel airflow system with low-profile radiator

Frame

Raised rail design for frame strength and basement storage

Tires

40': Michelin XRV 305/70R22.5 LRL
 43': Michelin X Line Energy Z 315/80R22.5 LRL

Wheels

(6) Aluminum wheels with Accu-Shield® finish and dress kit
 (2) Steel wheels on inside duals

Wheelbase

40": 245" + 48" tag
 43": 281" + 48" tag