Spartan® RV Chassis Advanced Protection System™ (APS):

- Automatic Traction Control (ATC)
- Adaptive Cruise Control (ACC)
- Electronic Stability Control (ESC)
- Collision Mitigation System (CMS)
- Mobileye® visual & audible lane departure warning
- Tire Pressure Monitoring System (TPMS)
- Spartan RV Chassis Safe Haul® (The industry’s premier factory-chassis integrated air supply for tow vehicle brake systems.)

Premium Features:

- Comfort Drive™ steering assist system w/ variable driver’s effort control feature
- Independent front suspension
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- Connected Coach® 15” HD widescreen glare-free digital dash display
- Variable Geometry Turbo (VGT), exhaust brake
- 10,000 lb towing capacity
- Rain sensing wipers
- Electronic suspension control system with self-leveling feature including air compressor for extended stays
- Tilt Tank Drain Assist
- Tri-Pod Steering Wheel with leather finish, phone, and media controls
- Headlamps with auto on/off feature
- Spartan RV Chassis Passive Keyless Start
- 20-Year Transferable Warranty on Frame & Cross Members
- 5-year/100,000-mile transferable warranty
- 5-year/100,00-mile Cummins Engine warranty
- 5-year/200,000-mile Allison Transmission warranty

Specifications:

Engine
Cummins L9
18.7 CFM Air Compressor
1,000 Watt Block Heater
Peak HP: 450 HP @ 2,100 rpm
Peak Torque: 1,250 lb-ft @ 1,200 rpm

Transmission
Allison 3000 MH

Chassis Ratings
GVWR: 38,600 lb
Front GAWR: 14,600 lb
Rear GAWR: 24,000 lb
GCWR: 48,600 lb

Suspension
Front: Independent air suspension with 14,600 lb capacity
Rear: Non-torque reactive parallelogram air suspension with 24,000 lb capacity

Shocks
Front: Koni
Rear: Koni

Brakes
ABS: WABCO 4S/4M with ESC
Front: Air disc
Drive: Air drum

Steering
Comfort Drive™ steering assist system with manual tilt & telescoping column

Fuel System
Fuel Tank: 90 gallon with dual fill
DEF Tank: 15 gallon

Electrical System
12v electrical system
Batteries: Two 950 cca
Alternator: 240 amp

Cooling System
Side-mounted radiator: parallel airflow system with low-profile radiator

Frame
Straight frame prep for Newmar STAR Foundation

Tires
Front: Michelin XRV 305/70R22.5 LRL
Rear: Michelin XRV 305/70R22.5 LRL

Wheels
(6) Aluminum wheels with Accu-shield® finish and dress kit
(2) Steel wheels on inside duals

Wheelbase
226”