Spartan® RV Chassis Advanced Protection System™ (APS):

- Automatic Traction Control (ATC)
- Electronic Stability Control (ESC)
- **OPTIONAL** Collision Mitigation System (CMS) with Adaptive Cruise Control (ACC)
- Tire Pressure Monitoring System (TPMS)
- Spartan RV Chassis Safe Haul® (The industry’s premier factory-chassis integrated air supply for tow vehicle brake systems.)

Premium Features:

- Comfort Drive™ steering assist system w/ variable driver’s effort control feature
- Variable Geometry Turbo (VGT) exhaust brake
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- 10,000 lb towing capacity
- Tri-Pod Steering Wheel with leather finish, phone, and media controls
- Connected Coach® 12.3” glare-free digital dash display
- Suspended adjustable pedals
- 20-Year Transferable Warranty on Frame & Cross Members
- 5-year/100,000-mile transferable warranty
- 5-year/100,00-mile Cummins Engine warranty
- 5-year/200,000-mile Allison Transmission warrant

Specifications:

Engine
Cummins L9
18.7 CFM Air Compressor
1,000 Watt Block Heater
Peak HP: 380 HP @ 2,200 rpm
Peak Torque: 1,150 lb-ft @ 1,200 rpm

Transmission
Allison 3000 MH

Chassis Ratings

	35’	38’
GVWR:	38,000 lb	38,600 lb
Front GAWR:	14,000 lb	14,600 lb
Rear GAWR:	24,000 lb	24,000 lb
GCWR:	48,000 lb	48,600 lb

Suspension
Front: Integrated air suspension and steer axle system with 14,600 lb capacity
Rear: Non-torque reactive parallelogram air suspension with 24,000 lb capacity

Shocks
Front: Koni
Rear: Koni

Brakes
ABS: WABCO 4S/4M with ESC
Front: Air disc
Drive: Air drum

Steering
Comfort Drive™ steering assist system with manual tilt & telescoping column

Fuel System
Fuel Tank: 100 gallon with dual fill
DEF Tank: 10 gallon

Electrical System
12v electrical system
Batteries: Two 950 cca
Alternator: 210 amp

Cooling System
Rear-mounted radiator: parallel airflow system with low-profile radiator

Frame
Raised rail design for frame strength and basement storage

Tires
Michelin XRV 305/70R22.5 LRL

Wheels
(4) Aluminum wheels with Accu-Shield® Finish and dress kit
(2) Steel wheels on inside duals

Wheelbase
35’: 212”
38’: 248”