Spartan® RV Chassis Advanced Protection System™ (APS):

- Automatic Traction Control (ATC)
- Electronic Stability Control (ESC)
- **OPTIONAL** Collision Mitigation System (CMS) with Adaptive Cruise Control (ACC)
- Tire Pressure Monitoring System (TPMS)
- Spartan RV Chassis Safe Haul® (The industry’s premier factory-chassis integrated air supply for tow vehicle brake systems.)

Premium Features:

- Comfort Drive™ steering assist system w/ variable driver’s effort control feature
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- Connected Coach® 12.3” glare-free digital dash display
- Passive steer tag axle
- 15,000 lb towing capacity
- 3-stage engine compression brake
- Tri-Pod Steering Wheel with leather finish, phone, and media controls
- 20-Year Transferable Warranty on Frame & Cross Members
- 5-year/100,000-mile transferable warranty
- 5-year/100,00-mile Cummins Engine warranty
- 5-year/200,000-mile Allison Transmission warranty

Specifications:

Engine
Cummins L9
18.7 CFM Air Compressor
1,000 Watt Block Heater
Peak HP: 400 HP @ 2,200 rpm
Peak Torque: 1,250 lb-ft @ 1,200 rpm

Transmission
Allison 3000 MH

Chassis Ratings

	40’	43’
GVWR:	44,600 lb	46,000 lb
Front GAWR:	14,600 lb	16,000 lb
Rear GAWR:	20,000 lb	20,000 lb
Tag GAWR:	10,000 lb	10,000 lb
GCWR:	59,600 lb	61,000 lb

Suspension
40’ Front: Integrated air suspension and steer axle system with 14,600 lb capacity
43’ Front: Trailing beam air suspension with 16,000 lb capacity
Rear: Non-torque reactive parallelogram air suspension with 20,000 lb capacity
Tag: Parallelogram air suspension and integrated passive steering tag axle with 10,000 lb capacity

Shocks
Front: Koni
Rear: Koni
Tag: Koni

Brakes
ABS: WABCO 6S/6M with ESC
Front: Air disc
Drive: Air disc
Tag: Air drum

Steering
Comfort Drive™ steering assist system with manual tilt & telescoping column

Fuel System
Fuel Tank: 100 gallon with dual fill
DEF Tank: 10 gallon

Electrical System
12v electrical system
Batteries: Two 950 cca
Alternator: 210 amp

Cooling System
Rear-mounted radiator: parallel airflow system with low-profile radiator

Frame
Raised rail design for frame strength and basement storage

Tires
40’: Michelin XRV 305/70R22.5 LRL
43’: Michelin X Line Energy Z 315/80R22.5 LRL

Wheels
(6) Aluminum wheels with Accu-Shield® finish and dress kit
(2) Steel wheels on inside duals

Wheelbase
40’: 245” + 48” tag
43”: 281” + 48” tag